## CADET COM-PAK SERIES HEATER

TEKSAN

- Efficient, quiet fan
- Warm up in a hurry with a fast-heating element
- Unique compact design is recess mounted into your wall to suit any room
- Heater assemblies and grilles are powder-coated to provide a durable finish, and complete heaters include a galvanized wall can
- Easy to install
- Rest easy – includes high temperature safety shutoff
- Available with or without built-in thermostat
- Conforms to UL Std. 2021 and Certified to CAN/CSA Std. C22.2 No. 46

The Com-Pak is an efficient, affordable way to add warmth without installing ductwork. Our hard wired heaters have proven safety features and multiple installation options, so your family can enjoy safe, sensible warmth for years.

### ARCHITECTURAL - ENGINEERING INFORMATION

Fan forced up flow electric air heaters are cULus listed, factory rated at 120V, 208V, and dual field rated 208V/240V. A 20 gauge galvanized steel wall mounting can with seven knockouts and 34 cubic inch wiring compartment is provided with each complete heater. Each heater is powder coated, of unitized construction and attaches to the wall can with a single screw and is self-contained and completely separate from the wall mounting can. Element is of nichrome type wire wrapped on mica insulators with a 16 amp rated, at 240V, high temperature manual power reset limit switch, and a one-time over temperature thermal back-up fuse, both located on the element board in the heated air flow for faster response time to abnormal conditions. A two stage centrifugal blower delivering approximately 40 to 55 CFM is driven by an impedance protected motor. The motor is totally isolated from the heating chamber. Metal grille is of one piece, 20-gauge construction and finished with a powder coat paint system.

### TECHNICAL INFORMATION

UL safety standards require the heater to be placed a minimum distance of 3/4 inches (1.9 cm) from adjacent surfaces and 4-1/2 inches (11.4 cm) from the floor. Manufacturer recommends installations 12 inches (30.5 cm) from all surfaces for longer and cleaner performance. All models 1500 watts or less may be ceiling mounted. A 3 foot (91.4 cm) minimum clearance is required for furniture or other objects placed directly in front of the heater.

Electric wall heaters and thermostats work best when installed on an inside wall.

Specifications are subject to change. © 2020 Glen Dimplex Americas.

**Glen Dimplex Americas** | 1.888.346.7539 | www.cadetheat.com

# COM-PAK

Grille: 9" W (22.9 cm) x 12"H (30.5 cm) x 1"D (2.5 cm)
Rough-in: 8"W (20.3 cm) x 10-1/8"H (25.7 cm) x 4"D (10.2 cm)
Thermostat temperature range 40°F to 85°F (4°C to 29°C)
Heater assemblies require a wall can and grille kit, and may require a thermostat

| PART | MODEL* | DESCRIPTION | WATTS | VOLTS | AMPS | BTUS | LBS/KGS |
|---|---|---|---|---|---|---|---|
| 67508<br>67580 | CSC101TW<br>CSC101TA | Complete unit with stat, wall can & grille, white or almond | 1000 | 120 | 8.3 | 3415 | 7/3.2 |
| 67509<br>67581 | CSC151TW<br>CSC151TA | " | 1500 | 120 | 12.5 | 5120 | 7/3.2 |
| 67505<br>67577 | CSC102TW<br>CSC102TA | " | 1000/750 | 240/208 | 4.2/3.6 | 3415/2560 | 7/3.2 |
| 67506<br>67578 | CSC152TW<br>CSC152TA | " | 1500/1125 | 240/208 | 6.3/5.4 | 5120/3840 | 7/3.2 |
| 67507<br>67579 | CSC202TW<br>CSC202TA | " | 2000/1500 | 240/208 | 8.3/7.2 | 6825/5120 | 7/3.2 |
| 67549<br>67503 | CSC101W<br>CSC101A | Complete unit without stat, with wall can & grille, white or almond | 1000 | 120 | 8.3 | 3415 | 7/3.2 |
| 67553<br>67504 | CSC151W<br>CSC151A | " | 1500 | 120 | 12.5 | 5120 | 7/3.2 |
| 67540<br>67535 | CSC072W<br>CSC072A | " | 750/563 | 240/208 | 3.1/2.7 | 2560/1925 | 7/3.2 |
| 67541<br>67536 | CSC102W<br>CSC102A | " | 1000/750 | 240/208 | 4.2/3.6 | 3415/2560 | 7/3.2 |
| 67543<br>67553 | CSC152W<br>CSC152A | " | 1500/1125 | 240/208 | 6.3/5.4 | 5120/3840 | 7/3.2 |
| 67544<br>67539 | CSC202W<br>CSC202A | " | 2000/1500 | 240/208 | 8.3/7.2 | 6825/5120 | 7/3.2 |
| 67550/67560 | CS051/CS051T | Heater assembly without/with thermostat | 500 | 120 | 4.2 | 1710 | 3.5/1.5 |
| 67515/67523 | CS101/CS101T | 120 volt | 1000 | 120 | 8.3 | 3415 | 3.5/1.5 |
| 67516/67524 | CS151/CS151T | " | 1500 | 120 | 12.5 | 5120 | 3.5/1.5 |
| 67563/67573 | CS058/CS058T | Heater assembly without/with thermostat | 563 | 208 | 2.7 | 1925 | 3.5/1.5 |
| 67564/67589 | CS078/CS078T | 208 volt | 750 | 208 | 3.6 | 2560 | 3.5/1.5 |
| 67557/67586 | CS108/CS108T | " | 1000 | 208 | 4.8 | 3415 | 3.5/1.5 |
| 67569/67598 | CS118/CS118T | " | 1125 | 208 | 5.4 | 3840 | 3.5/1.5 |
| 67571/67599 | CS158/CS158T | " | 1500 | 208 | 7.2 | 5120 | 3.5/1.5 |
| 67517/67525 | CS208/CS208T | " | 2000 | 208 | 9.6 | 6825 | 3.5/1.5 |
| 67584/67585 | CS052/CS052T | Heater assembly without/with thermostat | 500/375 | 240/208 | 2.1/1.8 | 1710/1280 | 3.5/1.5 |
| 67510/67518 | CS072/CS072T | 240/208 volt | 750/563 | 240/208 | 3.1/2.7 | 2560/1925 | 3.5/1.5 |
| 67511/67519 | CS102/CS102T | " | 1000/750 | 240/208 | 4.2/3.6 | 3415/2560 | 3.5/1.5 |
| 67512/67520 | CS122/CS122T | " | 1250/937 | 240/208 | 5.2/4.5 | 4265/3200 | 3.5/1.5 |
| 67513/67521 | CS152/CS152T | " | 1500/1125 | 240/208 | 6.3/5.4 | 5120/3840 | 3.5/1.5 |
| 67514/67522 | CS202/CS202T | " | 2000/1500 | 240/208 | 8.3/7.2 | 6825/5120 | 3.5/1.5 |

## CADET COM-PAK SERIES HEATER

TEKSAN

# COM-PAK TWIN

CADET
INVITING WARMTH

Grill: 16-1/4"W x 12"H x 1"D • Rough-in: 14-1/2"W x 10-1/8"H x 4"D
Thermostat temperature range 40°F to 85°F
Heater assemblies require CTC wall can, grill kit, and may require a thermostat

| PART | MODEL* | DESCRIPTION | WATTS | VOLTS | AMPS | BTUS | WT/LBS |
|---|---|---|---|---|---|---|---|
| 67526 | CSTC302TW | Complete unit with thermostat, wall can and grill, white or almond | 3000/2250 | 240/208 | 12.5/10.8 | 10240/7680 | 12 |
| 67582 | CSTC302TA | | | | | | |
| 67527 | CSTC402TW | " | 4000/3000 | 240/208 | 16.7/14.4 | 13650/10240 | 12 |
| 67583 | CSTC402TA | | | | | | |
| 67574 | CST308 | Heater assembly without thermostat | 3000 | 208 | 14.4 | 10240 | 6.5 |
| 67534 | CST308T | Heater assembly with thermostat | | | | | 7 |
| 67530 | CST408 | " | 4000 | 208 | 19.2 | 13650 | 6.5 |
| 67533 | CST408T | | | | | | 7 |
| 67528 | CST302 | " | 3000/2250 | 240/208 | 12.5/10.8 | 10240/7680 | 6.5 |
| 67531 | CST302T | | | | | | 7 |
| 67529 | CST402 | " | 4000/3000 | 240/208 | 16.7/14.4 | 13650/10240 | 6.5 |
| 67532 | CST402T | | | | | | 7 |

*Suffix W or A in model designates color