



ENERGY

11.1L

56100022
Rev: 1
Units
Std Metric

11.1L			
1500		1800	

General Engine Data						
Type	N/A		In-Line 4 cycle			
Number of cylinders	N/A		6			
Aspiration	N/A		Turbo Charge Air Cooled			
Bore	in	mm	4.84	123	4.84	123
Stroke	in	mm	6.1	155	6.1	155
Displacement	in^3	L	673	11.1	673	11.1
Compression Ratio	N/A		10.5			
Mean Piston Speed	ft/min	m/s	1525	7.75	1830	9.3
Gross Standby Power Rating^{1,2,3} Per ISO 3046 at the Flywheel						
NG	Hp	kW	268	200	315	235
LP	Hp	kW	180	134	208	155
MEP (@ rated Load on NG)	psi	bar	210	14	206	14
MEP (@ rated Load on LP)	psi	bar	141	10	136	9
Gross Prime Power Rating^{1,2,3} Per ISO 3046 at the Flywheel						
NG	Hp	kW	241	180	268	200
LP	Hp	kW	162	121	177	132
MEP (@ rated Load on NG)	psi	bar	189	13	175	12
MEP (@ rated Load on LP)	psi	bar	127	8.7	115	8.0
RPM Range (Min-Max)	RPM		1500-2000			
Rotation Viewed from Flywheel	N/A		Counter Clockwise			
Firing Order	N/A		1-5-3-6-2-4			
Dry Weight						
Fan to Flywheel	lb	kg	2600	1179	2600	1179
Rad to Flywheel	lb	kg	3125	1417	3125	1417
Wet Weight						
Fan to Flywheel	lb	kg	2695	1206	2695	2627
Rad to Flywheel	lb	kg	3377	1530	3377	1530
CG						
Distance from FW housing	in	mm	24	605	24	605
Distance above center of crankshaft	in	mm	6	160	6	160
Engine Mounting						
Maximum Allowable Bending Moment at Rear of Block	lb ft	N m	4425	6000	4425	6000
Moment of Inertia About Roll Axis	lb ft^2	kg m^2				
Flywheel housing	N/A		SAE No.1			
Flywheel	N/A		No. 14			
Number of Flywheel Teeth	N/A		152			
Exhaust System						
Type	Water Cooled Manifold					
Maximum allowable Back pressure	in HG	kPa	3	10.2	3	10.2
Standard Catalyst Back pressure	in HG	kPa	1.5	5.1	1.5	5.1
Exhaust Outlet Pipe Size						
Maximum Turbine Inlet Temperature	F	C	1382	750	1382	750
Exhaust Flow at Rated Power	lb/hr	kg/hr	1654	750	1869	848
Exhaust Flow at Rated Power @1350F	cfm	m^3/min	1261.13	35.7	1425	40.3
Air Induction System						
Maximum allowable Intake Air Restriction with Air Cleaner						
Clean	inH2O	kPa	5	1.24	5	1.24
Dirty	inH2O	kPa	15	3.74	15	3.74
Combustion Air required (entire engine)	lb/hr	kg/hr	1561	708	1764	800
Combustion Air required (entire engine)	cfm	m^3/min	396	11	448	13



ENERGY

11.1L

56100022	
Rev:	1
Units	
Std	Metric

11.1L			
1500		1800	

Electrical System							
Minimum Recommended Battery Capacity	AH		150				
Cold Cranking Current							
Engine only	CCA		900				
Engine with Drive train	CCA		900				
Maximum Allowable Resistance of Starting Circuit	Ohms		0.002				
Starting Motor Power	HP	kW	9.4	7	9.4	7	
Battery Charging Alternator							
Voltage	Volts		24				
Current	Amps		45				
Coil primary Resistance	Ohms		0.59Ω ± 10%				
Spark Plug p/n	IFR7F-4D						
Spark plug gap	inches	mm	.015" (-0/+ .008") .38mm (-0/+ .2mm)				
Cooling System							
Coolant Capacity							
Engine only	gal	L	5.5	25.0	5.5	25.0	
Engine with Radiator	gal	L	23	105	23	105	
Engine Coolant Flow	gal/min	L/min	69	260	82	310	
Water Pump Speed	RPM			1862		2235	
Heat rejected to Cooling water at rated Load	btu/min	kcal/sec	9285	39	11071	46.5	
Maximum Intake Air Temperature (IAT)	F	C	155	68	155	68	
ECU IAT Warning	F	C	140	60	140	60	
ECU IAT Shutdown	F	C	155	69	155	69	
Maximum Coolant Friction Head External to the engine	psi	bar	5.8	0.4	5.8	0.4	
Maximum Air Restriction Across a Radiator	inH2O	mmH2O	0.5	12.8	0.5	12.8	
Standard Thermostat Range							
Cracking Temperature	F	C	160	71	160	71	
Full Open Temperature	F	C	185	85	185	85	
Maximum Output Pressure of Engine Water Pump							
Maximum Allowable Pressure Cap	psi	bar	14.7	1	14.7	1	
Ambient Clearance Open Genset (water) (Air-to-Boil)							
Specified	F	C	142	61	142	61	
Actual	F	C			150	66	
Ambient Clearance (Oil)							
Specified	F	C	142	61	142	61	
Actual	F	C			139	59	
CAC Rise over Ambient (Charge)							
Specified	F	C	15	9	15	9	
Actual	F	C			4	2	
Maximum Allowable Top Tank Temperature	F	C	230	110	230	110	
ECU Warning	F	C	220	104	220	104	
ECU Shutdown	F	C	230	110	230	110	
Fan Power	HP	kW	5	4.0	9	6.7	
Fan Diameter, including blades	in	mm	38	965	38	965	
Fan Speed	RPM			1500		1800	
Cooling Fan Air Flow @ 1" Static H2O Pressure and 125F @ radiator	CFM	m ³ /min	15,429	437	18,000	510	
Charge Air Cooler							
Compressor Outlet Temperature	F	C	235	114	255	125	
Compressor Flow Rate per CAC	lb/hr	kg/hr	1654	750	1869	848	
Heat Rejection per CAC	btu/min	kW	TBD		1460	25.7	



ENERGY

11.1L

56100022

Rev: 1

Units

11.1L

Std Metric

1500

1800

Lubrication System							
Oil Specification	SAE 15W-40 Low Ash Gas engine oil (.25-.5% by wt), API CD/CF or higher						
Oil Pressure							
Idle							
Min	Psi	Bar	11	0.8	11	0.8	
Max	Psi	Bar	20.3	1.4	20.3	1.4	
Rated Speed							
Min	Psi	Bar	20.3	1.4	20.3	1.4	
Max	Psi	Bar	70	4.8	70	4.8	
Maximum Allowable Oil Temperature	F	C	250	121	250	121	
Engine Oil Capacity							
Min	Qts	L	20	19	20	19	
Max	Qts	L	26.5	25	26.5	25	
Oil Filter Capacity	Qts	L	3.75	3.5	3.75	3.5	
ECU Oil Pressure Warning ⁵	psi		30				
ECU Oil Pressure Shut Down ⁵	psi		25				
Fuel System							
Fuel Consumption ⁶							
NG	Ft ³ /hr	kg/hr	2028	41	2431	49	
LP	Ft ³ /hr	kg/hr	591	32	706	38	
Maximum EPR Rated Pressure	psi	kPa	1.0	6.9	1.0	6.9	
Maximum Running pressure to Electronic Pressure Regulator (EPR)	inH2O	kPa	11.0	2.7	11.0	2.7	
Minimum Running pressure to EPR	inH2O	kPa	7.0	1.7	7.0	1.7	
Minimum Gas Supply Pipe Size	2" NPT						
Maximum EPR Rated Pressure	psi	kPa	1.0	6.9	1.0	6.9	
Maximum Running Pressure to EPR	inH2O	kPa	11.0	2.7	11.0	2.7	
Minimum Running Pressure to EPR	inH2O	kPa	7.0	1.7	7.0	1.7	
Minimum LPG Supply Pipe Size ⁴	2" NPT						

¹Standby and overload ratings based on ISO3046.

² All ratings are gross flywheel horsepower corrected to 77°F at an altitude of 328feet with no cooling fan or alternator losses using heating value for NG of 1015 BTU/SCF.

³ Production tolerances in engines and installed components can account for power variations of +/- 5%. Altitude, temperature and excessive exhaust and intake restrictions should be applied to power calculations.

⁴ The preceding pipe sizes are only suggestions and piping sizes may vary with temperature, pressure, distance from supply and application of local codes. Gas must be available at adequate volume and pressure for engine at the EPR.

⁵ >1400RPM

⁶ See PSI Energy Technical Spec. 56100019 - Fuel Specification. Gas properties for fuel consumption data: NG: Density =0.717 kg/m3, LHV = 927 BTU/scf; Propane: Density = 1.882 kg/m3, LHV = 2316 BTU/scf