

*CIRCUIT BREAKER DATASHEET*



PRODUCT-DETAILS

XT4N 250 Ekip LSI In=150A 3p F F UL/CSA

XT4N 250 Ekip LSI In=150A 3p F F UL/CSA



**General Information**

Extended Product Type	XT4N 250 Ekip LSI In=150A 3p F F UL/CSA
Product ID	1SDA075421R1
EAN	8015644793982
Catalog Description	XT4N 250 Ekip LSI In=150A 3p F F UL/CSA
Long Description	C.BREAKER TMAX XT4N 250 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP-LSI R 150 A

**ABB EcoSolutions**

ABB EcoSolutions	Yes
------------------	-----

**Circular Value**

Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 58.5 %
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
End of Life Instructions	9AKK108468A2352
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

---

### Eco Transparency

---

Environmental Product Declaration - EPD	9AKK108468A1898
-----------------------------------------	-----------------

---



---

### Environmental

---

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

---



---

### Ordering

---

Order Code US and Canada	XT4NU3150FFF000XXX
EAN	8015644793982
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

---



---

### Dimensions

---

Product Net Width	105 mm
Product Net Height	160 mm
Product Net Depth / Length	82.5 mm
Product Net Weight	2.5 kg

---



---

### Container Information

---

Package Level 1 Units	box 1 piece
Package Level 1 Width	145 mm
Package Level 1 Height	210 mm
Package Level 1 Depth / Length	168 mm
Package Level 1 Gross Weight	2.5 kg
Package Level 1 EAN	8015644793982

---



---

### Additional Information

---

Circuit Breaker Type to be Associated	Power Distribution
Connecting Capacity Main Circuit	Busbar 85..200 mm²
Current Type	AC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	3
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 7.80 W
Product Main Type	SACE Tmax XT

Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I <sub>n</sub> )	150 A
Rated Frequency (f)	50/60 Hz
Rated Voltage (U <sub>r</sub> )	690 V AC
Rated Insulation Voltage (U <sub>i</sub> )	1000 V AC
Rated Operational Voltage	690 V AC
Rated Uninterrupted Current (I <sub>u</sub> )	250 A
Recommended Screw Driver	Main Circuit M8
Release	Ekip LSI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL
Sub-type	XT4
Suitable for Product Class	SACE Tmax XT
Terminal Connection Type	Front
Terminal Type	Bolt
Tightening Torque	8 N·m
Version	F
CAD Dimensional Drawing	1SDH002230A1003

### Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 65 A (480 V AC) 25 A (600 V AC) 18 A
-----------------------------------	-------------------------------------------------------

### Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	9AKK10103A3908
Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK106713A5529
UL Certificate	1SDL000163R0114
VDE Certificate	No certification needed
Dimension Diagram	1SDH000722R0100
Mechanical Drawings	1SDH000722R0100
Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000722R0003 1SDH000721R0506

### Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4932 >> 3 Pole Non-Interchangeable Trip Electronic Circuit Breakers
Object Classification Code	Q
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

